

**ALW 5.4**  
**Passive column speaker**

---



**Main features:**

- 2-way system
- 4 x 5"
- HF driver on CD horn
- High SPL
- Wooden enclosure
- Slim Design
- Exact dispersion

## **ALW 5.4**

### **Passive column speaker**

---

#### **System-overview:**

The ALW 5.4 is an elegant 2-way column loudspeaker for multifunctional use. Four high-performance 5" chassis with Neodymium magnets and long-excursion are time-aligned and symmetrically arranged following the D'Appolito principles around a high-performance ring-radiator with wave-plug. This enables a very wide horizontal coverage angle of 120°. The narrow vertical coverage generates a long outreach.

Operational safety is assured by electronic protection of the HF-driver.

Available as IP68-version on request.



## **ALW 5.4**

### **Passive column speaker**

---

#### **Technical Data:**

Configuration:	2-Way-fullrange-System, Bass reflex
Assembly:	4 x 5" neodymium-chassis 1 x HF-driver
Impedance:	8Ohm
Power handling	500/1000Watts
Dispersion horizontal:	120° (-6dB, 1kHz-8kHz)
Dispersion vertical:	30°
SPL (1W/1M):	98dB
SPL max:	130dB
Frequency response:	65Hz – 20kHz
Enclosure:	Plywood, powder coated
Connector:	Speakon®
Colour:	Standard RAL9005 black, any RAL colour available
Weight:	14kg
Dimensions:	H-800 x W-220 x D-190 (mm)
Accessories:	Horizontal and vertical wall mount brackets
Options:	RAL-colour, 100-Volt transformer Available as IP68-version on request