

## **ALPD 4.1**

### **Passive Column speaker**

---



The AIMLINE ALPD passive column speaker are developed specially for churches, conference-center and all public institutions, where high speech intelligibility over a long distance is required.

Thanks to its **d'Appolito** speaker design the ALPD series allows controlled narrow vertical bandwidth, so the AIMLINE ALPD series is the right choice for acoustically difficult installations to avoid unwanted reflections.

The small and unobtrusive enclosure is a fit for most architecturally sensitive environments.

The ALPD-series is always equipped with a tapped 100-Volt transformer and can also run with low impedance.

Aimline-ALPD-speaker can be ordered in any RAL-color to match the environment.

Multiple wall-mounting hardware is available.



## **ALPD 4.1**

### **Passive Column speaker**

---

#### **Technical Data**

Design: Full d'Appolito speaker arrangement

Drivers: 4 x 3,5" Chassis  
1 x 1" HF Neodymium

Power handling: 60 Watts / 8 Ohm

Transformer taps 100Volt: 30/15/7,5 Watts

Dispersion horizontally: 130°

Dispersion vertically: 35°

Frequency range: 100Hz – 20 kHz

Typical throw: 10m

Sensitivity: 95dB 1 W/1 M

Enclosure: Aluminum

Color: RAL 9016  
(all RAL-colors available as option)

Weight: 5kg

Dimensions: H-610 x W-105 x D-111 (mm)

Options: IP 65-Version on request